

VL-1708

17" 8 Port Rackmount LCD Monitors

Sales Information

Overview

17" LCD KVM SWITCH in 8 ports, combo support(USB/PS.2), combo cable included

VL-1708 is a LCD KVM Switch featuring an integrated 17" LCD panel, over-thin keyboard, and touchpad in a 1U rack-mountable Slideway™ housing.

With A Grade 17" TFT LCD, The highest resolution: 1920*1080 60HZ; the optimum resolution: 1280*1024 60HZ.

Compared with traditional keyboards, monitor and mouse, it could save almost 85% space.

Features

- Control platform with LCD, keyboard, mouse and multiple ports KVM switch.
- 1U height, suitable for 19" standard cabinet installation and metal structure.
- 17" LCD screen with high brightness, high clear and high resolution.
- Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees.
- Ultra thin keyboard with keypad.
- Mouse touch board with two function button.
- Front panel with lock to prevent damage by accident.
- Built-in Or External power.
- Automatic power on/off. When pulling control platform out from cabinet, the power turns off automatically. When pushing it into the cabinet, the power turns on automatically.
- An easy to use OSD menu.
- One control platform can control 8 computers by direct connection.
- One control platform can control 128 computers by 2 level cascade connection.



Specification

Type	VL-1708	
LCD Monitor	Monitor	17" SXGA Color TFT-LCD
	Active Area	337.920(H) x 270.336(V) mm
	Resolution(optimal)	1280*1024 60HZ
	Support Color	16.7M colors (RGB 6-bits + FRC data)
	White Luminance	300 (center, Typ) @ 7.5mA
	Contrast Ratio	1000 : 1 (Typ)
	Back-light	CCFL two lamps
	Pixel Pitch	0.264(per one triad) x 0.264
	LCD MTBF	50,000 hours
	Input power	DC 12V
Keyboard	Keyboard	105keys 88host keys + 17number keys
	Compatible IBM/AT	WIN95/98/98SE/ME/200/XP,VISTA,WIN 7,WIN NT,UNIX,LINUX.
	Port	Standard PS/2&USB
	Using life	>1.000.000 times
Mouse	X/Y resolution	1000dots/inch (40x40/mm)
	Hardware connector	Standard PS/2&USB
	OS support	WIN95/98/98SE/ME/200/XP,VISTA,WIN 7,WIN NT,UNIX,LINUX.
	Using life	>1.000.000 dots
Power built-in	Power input(AC)	~100V-240V
	Using life	MTBF>60,000 hours 25°C
Others	PC ports	8
	VGA resolution(highest)	1920*1080 60HZ
	VGA bandwidth	300MHz
	House color	Black
	House	Metal
	Gross weight	16.5KG
	Dimensions	446mm x 636mm x 42mm
	Rack installation depth	600mm ~ 1200mm(adjustable)
	Operating/Storage Temp.	0 ~ 50/-20 ~ -60 °C